

CB558

Size	TRA Code	Ply Rating	LUG #	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure	
								(kg)	(kPa)
4.00-8		B/4		15.0	3.00D	435	112	150	240
4.00-10		B/4		15.0	3.00D	485	112	185	240
5.00-12		B/4+		20.0	4.00D	590	145	280	200
5.00-12		B/4+		21.0	4.00E	590	145	280	200
6.00-12		C/6		22.0	4.50E	640	165	405	250
6.00-12		D/8		22.0	4.50E	640	165	520	330
6.00-14		C/6		24.0	4.50E	690	165	450	250
6.00-16		C/6		24.0	4.50E	745	165	495	250
6.50-16		C/6		24.0	5.00F	765	180	565	250
7.50-20	R-1	D/8	18	26.0	5.50F	910	205	900	280
9.5-20	R-1	D/8	16	31.0	W8	950	240	955	280
8.3-24	R-1	C/6	17	30.0	W7	995	210	810	240
9.5-24	R-1	D/8	18	31.0	W8	1050	240	1110	280
11.2-24	R-1	D/8	16	33.0	W10	1105	285	1225	240
12.4-24	R-1	D/8	17	36.0	W11	1160	315	1415	230
14.9-24	R-1	D/8	18	38.0	W13	1265	378	1760	180
14.9-26	R-1	E/10	19	38.0	W13	1315	378	2055	230
12.4-28	R-1	C/6	20	32.0	W11	1260	315	1275	170
12.4-28	R-1	D/8	20	32.0	W11	1260	315	1510	230
12.4-28	R-1	F/12	20	32.0	W11	1260	315	1930	350
13.6-28	R-1	F/12	20	43.0	W12	1310	345	2085	290
14.9-28	R-1	D/8	20	38.0	W13	1365	378	1880	180
16.9-30	R-1	D/8	20	41.0	W15L	1485	430	2245	170
16.9-30	R-1	F/12	20	41.0	W15L	1485	430	2730	240
18.4-30	R-1	F/12	20	43.0	W16L	1550	467	3180	230
30.5L-32	R-1	I/18	22	43.0	DW27A	1845	775	6000	210
16.9-34	R-1	D/8	23	41.0	W15L	1585	430	2380	170
16.9-34	R-1	E/10	23	41.0	W15L	1585	430	2605	200
18.4-34	R-1	F/12	21	43.0	W16L	1655	467	3375	230
18.4-38	R-1	E/10	23	43.0	W16L	1755	467	3165	180
18.4-38	R-1	F/12	23	43.0	W16L	1755	467	3575	230
20.8-38	R-1	E/10	22	43.0	W18L	1835	528	3475	160